







CAP



RECOMMEND P. C. B BOARD LAYOUT

PCB TOLERANCE: ±0.05 (TOP VIEW)

SPECIFICATIONS (规范)>>>

Current Rating (额定电流): 0.75Amps

Withstanding Voltage (耐电压): AC 500Vmin/Minute

Insulation Resistance (绝缘电阻): 1000MΩ Min

Contact Resistance (接触电阻): 20 mΩ MAX

Operation Temperature (工作温度): -40℃to+105℃

Material (材料)>>>

Plastic material (塑胶材质): PA6T/PA9T/LCP+30%GF

Color (塑胶颜色): Black


Insulator Material (绝缘材料): Polyester (UL94V-0)

Contact Material (接触材料): Brass

Contact Plating (接触电镀): Au 0s Sn over 40u" Ni

Dimension antitheses list(尺寸对照表)

项 目	H	PA	PB	PW	SQ	W
常规尺寸	1.38	2.8	1.9	4.6	0.3	3.0
客户需要						



电话(tel)	0755-23317175	深圳市熙宸电子科技有限公司 Shenzhen xichen Electronics Technology Co.,Ltd				
传真(fax)	0755-23010246					
单位(units)	MM	设计(draw)	王 刚	图名(name)	PH0.8x1.2mm 双排SMT	
比例(scale)	1 : 1	审核(ch'k)	陈晓俊			
版次(rev.)	A / 1	核准(app'd)	李新亮	料号(Part number)		
视图(view)		日期(date)		图档(File Name)		