








RECOMMEND P. C. B BOARD LAYOUT
PCB TOLERANCE: ± 0.05 (TOP VIEW)

SPECIFICATIONS (规范)>>>

Current Rating (额定电流): 1.0Amps
Withstanding Voltage (耐电压): AC 500Vmin/Minute
Insulation Resistance (绝缘电阻): 1000M Ω Min
Contact Resistance (接触电阻): 20 m Ω MAX
Operation Temperature (工作温度): -40°C to $+105^{\circ}\text{C}$
Material (材料)>>>
Plastic material (塑胶材质): PA6T/PA9T/LCP+30%GF
Color (塑胶颜色): Black
Insulator Material (绝缘材料): Polyester (UL94V-0)
Contact Material (接触材料): Brass
Contact Plating (接触电镀): Au 0s Sn over 40u" Ni

Dimension antitheses list(尺寸对照表)

项 目	H	PW	W				
常规尺寸	5.7	4.2 4.0	2.5				
客户需要							



电话(tel)	0755-23317175	 深圳市熙宸电子科技有限公司 Shenzhen xichen Electronics Technology Co.,Ltd					
传真(fax)	0755-23010246						
单位(units)	MM	设计(draw)	王 刚	图名(name)	PF1.27 单排SMT H5.7 型		
比例(scale)	1 : 1	审核(ch'k)	陈晓俊	料号(Part number)			
版次(rev.)	A / 1	核准(app'd)	李新亮	图档(File Name)			
视图(view)		日期(date)					